

Corrigendum

Corrigendum to: “Improved oxidation resistance of thermoelectric
skutterudites coated with composite glass”
[Ceramics International 39 (2013) 4551–4557]

Hongliang Dong^{a,b}, Xiaoya Li^a, Xiangyang Huang^a, Yanfei Zhou^a, Wan Jiang^c, Lidong Chen^{a,*}

^aCAS Key Laboratory of Materials for Energy Conversion, Shanghai Institute of Ceramics, Chinese Academy of Sciences,
1295 Dingxi Road, Shanghai 200050, China

^bUniversity of Chinese Academy of Sciences, No. 19A Yuquan Road, Beijing 100049, China

^cCollege of Materials Science and Engineering, Donghua University, 2999 North Renmin Road, Shanghai 201620, China

Available online 22 August 2013

On Page 4551, in the Introduction section, the middle part in the first paragraph should have read: The maximum efficiency of a thermoelectric generator can be described as follows:

$$\eta_{max} = \frac{[(T_h - T_c)/T_h][(1 + Z\bar{T})^{1/2} - 1]}{[(1 + Z\bar{T})^{1/2} + T_c/T_h]}$$

where T_h , T_c and $\bar{T}$ are the temperatures of the hot, cold junctions and average temperature of thermoelectric leg, respectively. These do not affect the results and conclusion.

DOI of original article: <http://dx.doi.org/10.1016/j.ceramint.2012.11.051>

*Corresponding author. Tel.: +86 2152414804; fax: +86 2152413903.

E-mail address: chenlidong@mail.sic.ac.cn (L. Chen).