

Erratum

Erratum to “The influence of failure criteria on strength prediction of ceramic components” [J. Eur. Ceram. Soc. 24 (2004) 2181–2186][☆]

Patrick Scheunemann*

Institute for Mechanical Engineering Design, Technical University of Hamburg-Harburg, Denickestrasse 17, 21073 Hamburg, Germany

Available online 15 April 2004

The publisher regrets that errors occurred in [Eq. \(2\)](#) and [Eq. \(7\)](#). The correct equations are shown below:

$$\sigma_{Ieq} = \frac{1}{2} \left[\sigma_n + \sqrt{\sigma_n^2 + 4 \left(\alpha_I \frac{Y_{II}}{Y_I} \tau_{eff} \right)^2} \right]. \quad (2)$$

$$I_{F2} = - \frac{\Delta(V_{eff}^{1/m})}{V_{eff}^{1/m} \cdot \Delta\mu} \Bigg|_{\substack{\mu_2 = 1 \\ \mu_1 = 0; \alpha_1 = 1; m = 10}} \quad (7)$$

[☆] doi of original article 10.1016/S0955-2219(03)00634-4.

* Tel.: +49-40-4-28-78-3674.

E-mail address: scheunemann@tuhh.de (P. Scheunemann).